



Right Labels, Right Time, Right Cost.



High Print
Speed



Expressive
Color



High-Capacity
200ml
Ink Tanks

MAKE LABELING SIMPLE

VP550 produces professional-quality labels for all your small-batch specialty products. Whether you are new to digital labeling or upgrading your thermal printer, these budget-friendly printers help you print brilliant color labels fast and timely in the correct quantity. And cost-effectively every time.

Key benefits:

- ✓ High Speed - Print 1,000 (6 x 4") labels in less than 10 min.
- ✓ Brilliant color quality Image
- ✓ Large individual ink tanks
- ✓ Enhanced water-resistant inks (with VP550)
- ✓ Food safe & Environmentally friendly dye ink formula

Print all you need in one-step!

Brilliant color
images

We recommend the
VP550 (with Enhanced
water-resistant inks) for
product labels that are
exposed to moisture.
(e.g. chilled/refrigerated
food)



Fine text, barcode

Variable data

Asia Office
Email: asia@vipcolor.com
Phone: +65 6482 1755
Web: vipcolor.com

China Office
Email: asia@vipcolor.com
Phone: +86 21 3898 4898 x 8210
Web: vipcolor.com/zh

Europe Office
Email: info@vipcoloreurope.com
Phone: +34 93 588 3018
Web: vipcoloreurope.com

US Office
Email: sales@vipcolor.com
Phone: 1 800 404 3185
Web: vipcolor.com

TECHNICAL SPECIFICATIONS

VP550	
Print speed	6 and 8 ips (154 and 203 mm/second)
Print resolution	1,600 x 1,600 dpi and 1,600 x 800 dpi
Print width/Length	2" - 8.5" (51 - 216 mm) / Up to 40" (1.016 m)
Comm ports	USB 2.0, 10/100Base-T, GPIO
Inks	Five Individual 200ml (Enhanced water resistant) dye
Time to first label	Less than 10 seconds
Print modes	Roll-to-Cut, Roll-to-Roll, Print & Hold
Barcode PQ	Grade B or better for <ul style="list-style-type: none"> • 1D barcode (Code 39) with 10 mils bar width • 2D barcode (PDF417) with 10 miles cell size
Electrical	Universal power supply - 100-240 Vac, Peak current < 4A
Temperature	Operation: 15 to 35°C at RH 20 -80%; Storage: -5 to 50°C
Safety/ Compliant	FCC Part 15, Subpart B, Class A (US), cULus, IEC-62368-1, RCM, CCC, UKCA mark, Singapore Safety Mark
User Interface	Embedded web server, Backlit LCD control panel in 9 languages, LED for warning and readiness indication
Acoustics	Sound pressure level < 60 dBA
Printer Driver	Windows™ 10 and above
Supported Software	All major Windows based label and graphic design applications like Adobe Illustrator, Nicelabel, Bartender.
Sensor type	Gap, Reflective sensor for black mark
Media type	Roll (continuous, die-cut), fan-fold
Media thickness	0.1 - 0.3 mm
Roll diameter	8" (203 mm) OD with 3" (76 mm) core
Supported media	Glossy, matte, synthetics
Others	Rugged metal casing, automatic cutter, patented print & hold mechanism
Warranty	1 year warranty or 5M inches, whichever earlier

Label Printer comes with unwinder

Weight: 66 lbs (30kg)




- High Speed Print
- Brilliant color quality Image
- Fine text, barcode and variable data



PRINTING YOUR OWN LABELS IS AS SIMPLE AS ABC



Design the label



Load the blank labelstock



Print the label




Paste on your product

ACCESSORIES



Re-winder



Label Slitter



Matrix Remover & Slitter



Scan the QR code to learn how Babe Farms overcame its labeling challenges, innovate and develop new products faster than ever with high-quality labels printed with the VIPColor printer.



SCAN ME to schedule a demo today!

